

DCI-3000

Digital Cinema Integrated Projection System

A complete one-stop digital cinema solution with Barco DLP Cinema® projector



DCI-3000 Digital Cinema Integrated Projection System

“ GDC Technology took another major step forward in its D-Cinema technology by developing the **DCI-3000 Digital Cinema Integrated Projection System**. The DCI-3000 integrated projection system features a Barco DLP Cinema® projector and GDC Technology

- SX-3000 Standalone Integrated Media Block™ or
- SX-2000AR/TR Digital Cinema Server with New Integrated Media Block


providing a complete one-stop solution for digital cinema. ”



DCI-3000 Digital Cinema Projection System

A complete one-stop digital cinema solution with Barco DLP Cinema® projector

Key Benefits



1

Lower Maintenance Costs¹

The DCI-3000 eliminates the need for an external file server and comes with SMS software for playback control and content management.

2

High Frame Rate

The DCI-3000 supports high frame rate content in 2D and 3D (48 & 60fps per eye).

3

All Image Resolution

The DCI-3000 supports SD, HD, 2K and 4K (optional) resolution.

4

Comprehensive Support for Alternative Content

The DCI-3000 supports HDMI input, 3G-SDI input and network live streaming² (optional). It also supports image scaling to 2K.

5

Live 3D Support² (Optional)

The DCI-3000 comes integrated with 3D Demuxing (side-by-side) which makes receiving high-quality 3D broadcasts possible. It also provides a built-in integrated 3D decoder to seamlessly support 3D Live broadcast without requiring additional decoder.

6

Supports All Approved 3D Systems

The DCI-3000 seamlessly integrates with numerous studio-approved 3D systems such as RealD, MasterImage, Dolby 3D and active 3D systems.

7

Remote Access and Monitoring

Cinema operators can remotely access the DCI-3000 using the Theatre Management System (TMS) and Screen Management System (SMS) from a Windows® PC and/or smart phones.

8

One-stop Installation, Service and Maintenance

No messy and expensive wiring work. Rely on GDC Technology for one-stop service and maintenance without the need to make numerous calls to different vendors.

Technical Specifications

Server/IMB Specifications

Video Specifications

JPEG 2000	4K – 24 (2D) (optional) 2K – 24, 48, 60 (2D) 2K – 24, 48, 60 (3D) SD/HD
MPEG 2/MPEG 4 ³ Packaging	SMPTE Digital Cinema Package (DCP), Interop DCP

Audio Output

Digital uncompressed audio	16/24-bit AES/EBU, 16 channels, 48/96 KHz 2 x RJ45
----------------------------	--

System Interfaces

Ethernet	SX-3000 : 2 x RJ-45 (1000 BaseT) SX-2000AR/TR : 3 x RJ-45 (1000 BaseT) x 3 (external storage)
eSATA	2 x USB A-Type Female
USB 2.0	In & Out (2 x BNC)
LTC	Passive loop output/ Video sync input (2 x BNC)
REF	x 1 (alternative content input) x 2 (alternative content input)
HDMI	4 x RJ45 (8 GPIs and 8 GPOs)
3G-SDI	Read speed 8x
8-port GPI/Os (optional)	CRU-Dataport
DVD-ROM drive ⁴	
CRU sled ⁴	

Server Diagnostics

Via PC touch panel
Via SNMP agent

Security

AES 128-bit encrypted data storage
Civolution (NexGuard®) forensic
watermarking

Subtitles

Subtitle overlay³
Projector Cinecanvas support

User Interface

PC/ Mac/ VGA/ SX-2000 server control

Power

Power requirement ⁴	100 to 240V, 60 to 50Hz, 6 to 3A
Max power consumption	SX-3000 : 75W SX-2000AR/TR : 395W
Redundant power supplies ⁴	Redundant internal hot swappable x 2
Uninterrupted power supply (UPS) with surge protection (optional) ⁵	3-way, meets IEEE STD 587 Cat. A 6KV test

Physical

Dimensions (Server) ⁴	482(W) x 616(D) x 177(H) mm 4RU
Weight (Server) ⁴	25kg (55lbs)
Dimensions (IMB)	320(W) x 240(D) x 63.7(H) mm
Weight (IMB)	1.5kg

Environmental

Operating temperature	35°C / 95°F
Operating humidity	20% to 90%, non-condensing
Operating altitude	10,000 ft. above sea level

Third-party Integration Options

TMS	GDC, Third-party ⁵
3D System	RealD, Dolby 3D, MasterImage, active systems
4D system	D-BOX Motion Code™, 4D plex
3D sound	Dolby Atmos ⁴
Closed Captioning Device	Support SMPTE430-10



Powering your digital cinema experience

Projector Specifications

Digital MicroMirror Device™	DCI-3000-S2K8/S2K10 : 3 x 0.69" DC2K dark metal devices DCI-3000-12C/15C/20C : 3 x 0.98" DC2K dark metal devices DCI-3000-19B/23B/32B : 3 x 1.2" DC2K dark metal devices DCI-3000-4K2/4K3 : 3 x 1.38" DC4K dark metal devices
Native resolution	DCI-3000-S2K8/S2K10/12C/15C/20C/19B/23B/32B : 2,048 x 1,080 pixels DCI-3000-4K2/4K3 : 4,096 x 2,160 pixels
Housing	Hermetically sealed DMDs and optical assembly
Screen Width	DCI-3000-S2K8 Screen width (screen gain 1.0) @ 14ftl: up to 8m (26ft) DCI-3000-S2K10 Screen width (screen gain 1.2) @ 14ftl: up to 10m (33ft) DCI-3000-12C Screen width (screen gain 1.2) @ 14ftl: up to 12m (39ft) DCI-3000-15C Screen width (screen gain 1.4) @ 14ftl: up to 15m (49ft) DCI-3000-20C Screen width (screen gain 1.8) @ 14ftl: up to 20m (65ft) DCI-3000-19B Screen width: 19m (62ft) DCI-3000-23B/4K2 Screen width: 23m (75ft) DCI-3000-32B/4K3 Screen width: 32m (105ft)
Pedestal	Universal pedestal (optional)
Max. Ambient Temperature	35°C / 95°F
Lamp Power	DCI-3000-S2K8 : 1.6kW (short-arc Xenon lamp) DCI-3000-S2K10 : 2.2kW (short-arc Xenon lamp) DCI-3000-12C : 1.2kW - 2kW (Xenon lamp) DCI-3000-15C/19B : 1.2kW - 3kW (Xenon lamp) DCI-3000-20C/23B/4K2 : 1.2kW - 4kW (Xenon lamp) DCI-3000-32B/4K3 : 3kW - 7kW (Xenon lamp)
Contrast	DCI-3000-S2K8/S2K10 : 1850:1 DCI-3000-12C/15C/20C/19B/23B/32B/4K2/4K3 : 2000:1
Digital Video Inputs	DCI-3000-12C/15C/20C/19B/23B/32B/4K2/4K3 Slot for 2 x SMPTE 292M inputs or 4K Integrated Media Block 2 x DVI input both selectable as single and dual link
Prime Lenses	DCI-3000-S2K8/S2K10 Fully motorized, 1.2 - 1.7, 1.34 - 1.9, 1.5 - 2.15, 1.7 - 2.55, 2.0 - 3.9 DCI-3000-12C/15C/20C 1.2 - 1.8, 1.4 - 2.05, 1.6 - 2.5, 1.95 - 3.2, 2.4 - 3.9 DCI-3000-19B/23B/32B 1.25 - 1.45, 1.4 - 2.05, 1.6 - 2.35, 1.8 - 2.8, 2.15 - 3.6, 2.8 - 5.5 DCI-3000-4K2/4K3 1.13-1.31, 1.27-1.86, 1.45-2.13, 1.63-2.53, 1.95-3.26, 2.53-4.98 equivalent throw ratios for 4K 1.38" DMD
Projector Diagnostics	via PC touch panel via Communicator control software via Communicator LITE control software (web-based) ⁶ via SNMP agent

Power Requirements	DCI-3000-S2K8/S2K10/12C/15C/20C/19B/23B : 220V DCI-3000-32B 3x 400V + N or 3 x 220V 30,000 BTU/hr (with 6.5kW lamp) DCI-3000-4K2 200-240V 30A 50-60Hz 19,000 BTU/hr (with 4kW lamp) DCI-3000-4K3 3W+N+PE 230/400V 16A 50-60Hz or 3W+PE 208V 27A 50-60Hz 30,000 BTU/hr (with 6.5kW - 7kW lamp)
Dimensions	DCI-3000-S2K8/S2K10 325(H) x 626(W) x 925(D) mm 12.8(H) x 24.7(W) x 36.4(D) inch DCI-3000-12C/15C/20C 558(H) x 694(W) x 1034(D) mm 22.0(H) x 27.3(W) x 40.7(D) inch DCI-3000-19B/23B/32B/4K2/4K3 604(H) x 754(W) x 1129(D) mm 23.78(H) x 29.69(W) x 44.45(D) inch <i>NB: min. 5cm of air inlet spacing required at the bottom of projector</i>
Weight	DCI-3000-S2K8/S2K10 Recessed handles for easy carrying lamp-house removed- 56.5 kg (125 lbs) for carrying total weight- 66.5 kg (147 lbs) DCI-3000-12C : 100kg (220lbs) DCI-3000-15C/20C : 102kg (225lbs) DCI-3000-19B/23B : 133 kg (293 lbs) DCI-3000-32B : 140 kg (309 lbs) DCI-3000-4K2 : 134 kg (295 lbs) DCI-3000-4K3 : 141 kg (311 lbs)
Options	DCI-3000-S2K8/S2K10 3D add-ons Touch screen monitor DCI-3000-12C/15C/20C/19B/23B/32B/4K2/4K3 ACS-2048 3D add-ons Touch panel
Standard Features	DCI-3000-S2K8/S2K10 CLO (Constant Light Output) Powerful SNMP agent Full 2K triple flash 3D DCI-3000-12C/15C/20C/19B/23B/32B/4K2/4K3 CLO (Constant Light Output) Powerful SNMP agent HDCP support Full 2K triple flash 3D Advanced patented DMD cooling ⁷

¹ Only available in SX-3000

² Depending on specifications - please check with GDC Technology sales representatives

³ Feature may not be available upon initial release

⁴ Only available in SX-2000AR/TR

⁵ Please check with your TMS provider

⁶ Only available in DCI-3000-S2K8/S2K10

⁷ Only available in DCI-3000-4K2/4K3

DCI-3000 Model Options

The DCI-3000 Digital Cinema Integrated Projection System is available in various configurations to suit your differing needs.

Server/ IMB Model	Projector Model	DCI-3000 Model No.
SX-3000	DP2K-8S	DCI-3000-S2K8
SX-3000	DP2K-10S	DCI-3000-S2K10
SX-3000	DP2K-12C	DCI-3000-12C
SX-3000	DP2K-15C	DCI-3000-15C
SX-3000	DP2K-20C	DCI-3000-20C
SX-3000	DP2K-19B	DCI-3000-19B
SX-3000	DP2K-23B	DCI-3000-23B
SX-3000	DP2K-32B	DCI-3000-32B
SX-3000	DP4K-23B	DCI-3000-4K2
SX-3000	DP4K-32B	DCI-3000-4K3

Server/ IMB Model	Projector Model	DCI-3000 Model No.
SX-2000AR/TR	DP2K-8S	DCI-3000AR/TR-S2K8
SX-2000AR/TR	DP2K-10S	DCI-3000AR/TR-S2K10
SX-2000AR/TR	DP2K-12C	DCI-3000AR/TR-12C
SX-2000AR/TR	DP2K-15C	DCI-3000AR/TR-15C
SX-2000AR/TR	DP2K-20C	DCI-3000AR/TR-20C
SX-2000AR/TR	DP2K-19B	DCI-3000AR/TR-19B
SX-2000AR/TR	DP2K-23B	DCI-3000AR/TR-23B
SX-2000AR/TR	DP2K-32B	DCI-3000AR/TR-32B
SX-2000AR/TR	DP4K-23B	DCI-3000AR/TR-4K2
SX-2000AR/TR	DP4K-32B	DCI-3000AR/TR-4K3

GDC Technology Offices

Hong Kong (Headquarters)

Unit 1-7, 20th Floor,
Kodak House II,
39 Healthy Street East,
North Point, Hong Kong
Tel : +852 2507 9555

China (Beijing)

Rm. 609-618, Office Building,
20# Xinde Street,
Xicheng District,
Beijing, P.R. China 100088
Tel : +86 10 6205 7040

China (Shenzhen)

Room A701, 7/F,
Languang Technology Building,
No.7 Xinxu Road,
North Zone,
Hi-Tech Park,
Nanshan District,
Shenzhen, P.R. China
Tel : +86 755 8608 6000

Spain (Barcelona)

Edificio Mercurio,
Vía Augusta, 59, desp. 607,
08006 Barcelona, Spain
Tel : +34 93 159 51 75

Peru (Lima)

Calle Rey Bahamonde N°111,
Santiago de Surco,
Lima 33 - Peru
Tel : +51 1 677 6708

USA (Los Angeles)

1016 West Magnolia Boulevard,
Burbank, CA 91506, USA
Tel : +1 818 972 4370 /
+1 877 743 2872 (Toll Free)

Singapore

10 Ubi Crescent,
Ubi Tech Park,
Lobby B, #06-25,
Singapore 408564
Tel : +65 6222 1082

Indonesia (Jakarta)

Total Building Lantai 4 Suite 0401,
Jl. Letjen S. Parman Kav. 106A,
Kel. Tomang,
Kec. Grogol Petamburan,
Jakarta Barat 11440

Japan (Tokyo)

3F, Kyobashi-Chuo Bldg,
1-14-7 Kyobashi Chuo-ku,
Tokyo 104-0031, Japan
Tel : +81 3 5524 3607

India (Mumbai)

Office No. B-207/208,
Everest Chamber,
Andheri Kurla Road,
Marol, Andheri (East),
Mumbai, 400059, India
Tel : +91 22 4044 0500

Mexico (Mexico City)

Ave. Santa Fe 94,
Torre A Piso 8,
Col. Zedec Santa Fe,
Alvaro Obregon,
Mexico, D.F.,
C.P. 01210 Mexico
Tel : +52 55 8851 1198 /
+52 55 8851 1165

Email : info@gdc-tech.com

Website : www.gdc-tech.com



GDC Technology manufacturing facility is ISO 9001 : 2008 certified.

Copyright © 2015 GDC Technology Limited. All rights reserved. All trademarks listed in this brochure are properties of their respective owners. Specifications are subject to change without notice due to ongoing product development and improvement.